

107525475
Rec'd PCT/PTO 23 FEB 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/021444 A1

(51) International Patent Classification⁷: **H01L 27/146**

(21) International Application Number:
PCT/IB2003/003752

(22) International Filing Date: 31 July 2003 (31.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02078601.8 30 August 2002 (30.08.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FOLKERTS,**


Hein, O. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **MAAS, Joris, P., V.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **VERBUGT, Daniel, W., E.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **LUKIYANOVA, Natalia, V.** [RU/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **HERMES, Daniel, H., J., M.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **HOEKSTRA, Willem** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **MIEROP, Adrianus, J.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **DUIJVESTIJN, Adrianus, J.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,

[Continued on next page]

(54) Title: **IMAGE SENSOR, CAMERA SYSTEM COMPRISING THE IMAGE SENSOR AND METHOD OF MANUFACTURING SUCH A DEVICE**



a



b

(57) Abstract: An image sensor (1) having a semiconductor body (2) with a first conductivity type and having a surface (3), the surface being provided with a number of cells (4), a cell comprising a photosensitive element (5) and a reset transistor (6), the reset transistor comprising a source region (7), a drain region (8) and a gate region (9), the source region (7) and the drain region (8) having a second conductivity type opposite to the first conductivity type, the source region (7) of the reset transistor (6) being electrically connected to the photosensitive element (5). There is a well region (10) present which well region extends from the surface (3) into the semiconductor body (2) and extends at least partly below the gate region (9) and the well region has a first conductivity type. The source region (7) extends at least substantially in a doped region (11) of the photosensitive element (5), the doped region (11) having a second conductivity type. The reduction of the source-well junction area reduced the number of white pixels and fixed pattern noise. In the method of manufacturing the image sensor, the well region (10) is

positioned partly below the gate region (9) so that there is a distance (13) between the highly doped source region (7) and the well region (10). The distance (13) increases the depletion layer width between the source and well junction, so that tunnel currents no longer dominate the leakage currents and the related number of white pixels and fixed pattern noise are reduced.

WO 2004/021444 A1